SC METROMAT SRL

Compartimentul Comercial: 505600 - Sacele - Piata Libertatii nr.2 - tel/fax: 0268 275 212; 0268 276 807 e-mail: sales@metromat.ro - comert@metromat.ro

Dezumidificator pt camere de 15 m³ sau 37m³, TTK 24E.

COMFORT DEHUMIDIFIER TTK 24 E

Convenient dehumidification without rough edges

In all smaller rooms its compact dimensions, the superb performance and its excellent design make the TTK 24 E an agreeable team player all around.

And best of all: it can be controlled with only one button. Just connect it to the mains, switch it on, all done – the workings of TTK 24 E are very simple and at the same time extremely efficient. For it removes a considerable amount of humidity: in 24 h up to 10 litres in smaller rooms to a size of 15 m².

The comfort dehumidifier TTK 24 E comes with all the convenient equipment features enabling it to perform its duty basically unattended: among these are the electronic automatic defrost function, the filling level warning light to indicate a full water tank as well as the overflow protection function with automatic switch-off.

Moreover, it can even be applied where regular manual emptying of the water tank cannot always be conveniently effected e.g. in heated basements. For this purpose the TTK 24 E is equipped with an integrated separate hose connection through which the condensate can directly be discharged into a drain.


Standard features:

- ***Automatic air circulation defrost system***
- ***Filling level warning light to indicate a full water tank***
- ***Overflow protection with automatic switch-off***
- ***Connection for external condensation draining***
- ***Integrated air filter – washable – for additional air purification by extraction of dust or animal hair***



Special features:

- Simple mode of dehumidification
- Excellent design
- Easy handling
- Low-maintenance construction



Which device is suited for which room size? For each comfort dehumidifier a specific performance chart regarding the suitability is to be found here. From it you can read the room size directly with area and volume ranges. Click to enlarge the chart in a new window...

TECHNICAL DATA

General information		
	Article number	1.120.000.024
Dehumidification performance		
	At 30 °C / 80 % RH [l/24h]	8.56
	Max. [l/24h]	10
Amount of air		
	Stage Max. [m³/h]	100
Recommended room size construction drying		
	m³	—
	m²	—
Recommended room size dry keeping		
	m³	37
	m²	15
Surrounding conditions		
	Min. temperature range [°C]	5
	Max. temperature range [°C]	32
	Min. humidity range [% RH]	20
	Max. humidity range [% RH]	80
Electrical values		
	Mains connection	230 V/50 Hz
	Nominal current consumption [A]	1.2
	Power input [kW]	0.25
	Recommended fusing [A]	10
	Required current starting phase [A]	—
Electrical values		
	Mains connection	230 V/50 Hz
	Nominal current consumption [A]	1.2
	Power input [kW]	0.25
	Recommended fusing [A]	10
	Required current starting phase [A]	—
Electric connection		
	Connection plug	CEE 7/7
	Cable length [m]	1.8
Compressor		
	Reciprocating piston compressor	■
	Rotary piston compressor	—
	Type of cooling agent	R-134a
	Amount of cooling agent [g]	62
	GWP factor	1,430
	CO_2 equivalent [t]	0.089
	Suction Side pressure [MPa]	0.4
	Discharge Side Pressure [MPa]	1.2
Water tank		
	Contents in [l]	1.6
Sound values		
	Distance 1 m [dB(A)]	42
Dimensions		
	Length (packaging excluded) [mm]	243
	Width (packaging excluded) [mm]	312
	Height (packaging excluded) [mm]	410

Weight		
	(packaging excluded) [kg]	10

EQUIPMENT, FEATURES AND FUNCTIONS		
Automatic defrosting		
	Electronic	■
	Hot gas	—
Automatic dehumidification		
	Non-stop dehumidification	■
	Analogue hygrostat	—
	Electronic hygrostat	—
	Program-controlled	—
Fan		
	Axial	■
	Radial	—
	stages	1
Condensate tank monitoring		
	Container available	■
	Shut-off when full	■
	Indicator container full	■
Room air filter		
	Readily accessible	■
	Cleanable	■
	Ionizer selectable	—

NOTA: Aceasta fisa a fost realizata sub rezerva modificarilor ulterioare de ordin tehnic sau a erorilor de editare.

Fotografia are caracter informativ.

NOTE: Products and specifications are subject to change without prior notice .Pictures may differ from original.