release date: 17-Oct-17

SC METROMAT SRL

Compartimentul Comercial: 505600 - Sacele - Piata Libertatii nr.2 - tel/fax: 0268 275 212; 0268 276 807
e-mail: sales@metromat.ro - comert@metromat.ro

Pompa de inalta presiune hiraulica, ADT 928



The 928 is an ideal comparison test pump for calibrating pressure measuring instruments such as test gauges, indicators or transducers in the field or laboratory.

The Additel 928 Hydraulic Pressure Test Pump is a hand operated pressure pump designed to generate pressure to 15,000 psi (1,000bar). This pump incorporates a dual-piston system which is ideal for filling large volume workload with the hand pump and providing smooth increase and decrease of pressure with the fine adjustment. The Additel 928 Test hand pump incorporates an isolation valve which isolates the calibration volume from the check valve associated with the hand pump. Because the check valve can often be a source of leaks and maintenance, the isolaton valve provides more stable measurements and reduces potential maintenance of the pump. Two hand-tight quick connectors installed on the pump allow easy connecting and disconnecting to the test pump without the need for PTFE tape or wrenches. The Additel 928 is an ideal comparison test pump for calibrating pressure measuring instruments such as test gauges, indicators or transducers in the field or laboratory.

Additel 928 Hydraulic Pressure Test Pump

Oil/Water: 0 to 15,000 psi



- **Pressurize large-volume workload**
- **Generate to 15,000 psi (1,000 bar) pressure**
- **Portable only 8.6 lbs (3.9kg)**
- **Increase and decrease pressure smoothly**
- **Hand-tight quick connectors**

- **Media:**
  Mineral oil or deionized water. *(oil is default media liquid. Pump with water as media to be ordered specifically).*

- **Generated Pressure Range**
  0 to 15,000 psi (1,000 bar) gauge pressure.

- **Ram/ adapter Material:** 304 SS
- **Body:** 304 SS / aluminum
- **Seals:** Buna-N / PTFE / Copper Alloy
- **Reservoir:** UPVC

- **Connections**
  Hand-tight connectors for both test gauge and reference gauge.
  Test gauge connection:1/4" NPT female, 1/4" BSP female, or M20*1.5 female
  Reference gauge connection:1/4" NPT female, 1/4" BSP female, or M20*1.5 female

- **Dimensions**
  Height:6.38"(162mm) Base:13.58" (345mm) *8.46" (215mm)

- **Weight:** 8.6 lbs (3.9kg)

- **Warranty:** one year

- **Piston Volume:** Fine adjust piston volume:0.9ml (0.05 in3)

- **Reservoir Volume:** 150ml (9.15 in3)

NOTA: Aceasta fisa a fost realizata sub rezerva modificarilor ulterioare de ordin tehnic sau a erorilor de editare.

Fotografia are caracter informativ.

NOTE: Products and specifications are subject to change without prior notice .Pictures may differ from original.