SC METROMAT SRL

Compartimentul Comercial: 505600 - Sacele - Piata Libertatii nr.2 - tel/fax: 0268 275 212; 0268 276 807 e-mail: sales@metromat.ro - comert@metromat.ro

Dezumidificator 345m³h, TTK127 E.



COMFORT DEHUMIDIFIER TTK 127 E

State-of-the-art comfort backed by a functional design

TTK-E-S Standard series COMFORT

A functional design pleasing to the eye, technical equipment – remarkably convenient and modest pricing: As a special highlight, the dehumidifier TTK 127 E has an extra comfort function.

Optimum room climate at all times – simply at the push of a button. Fitted with a comfort button the TTK 127 E automatically regulates the humidity value to the most agreeable level depending on the temperature. At most, the dehumidifier strips the ambient air from up to 50 litres of moisture per day and is suited for room sizes of up to 150 m². Naturally, the dehumidifier is also equipped with a hygrostat-controlled automatic dehumidification system, for which a fixed target humidity value is selected in advance. When this value is exceeded, the dehumidifier automatically switches itself on and then off again to save energy as soon as the desired target value has been reached.

A mode for drying laundry ensures that your wet clothes dry faster, moisture is extracted from carpeting or shoe racks are kept dry.

Owing to further convenient features handling the TTK 127 E is as easy as winking. For instance, the device comes with handy functions such as a timer control and two fan stages, overflow protection with automatic switch-off as well as an easily accessible and washable air filter.

The large condensation tank has a capacity of 6 litres, which conveniently reduces the draining frequency. Also integrated in the TTK 127 E is a separate connection through which the condensate can be discharged directly by means of a hose – e.g. for unattended permanent drying operations in your holiday home or on your boat.

Special features:

- Particularly easy handling
- Comfort mode for the temperature-dependent automatic humidity control for an optimum room climate at all times
- Display of current humidity values
- Mode for drying laundry
- Filter cleaning indicator

Standard features:

- ***Hygrostat control with real-value humidity selection***
- ***Selectable full automation or permanent operation***
- ***Filling level warning light to indicate a full water tank***
- ***Cable winder***
- ***comfort function***
- ***Timer function***
- ***Two fan stages***
- ***Overflow protection with automatic switch-off***
- ***Connection for external condensation draining***



TECHNICAL DATA		
General information		
	Article number	1.120.000.126
Dehumidification performance		
	At 30 °C / 80 % RH [l/24h]	46.8
	Max. [l/24h]	50
Amount of air		
	Stage Max. [m³/h]	345
Recommended room size construction drying		
	m³	180
	m²	78
Recommended room size dry keeping		
	m³	375
	m²	150
Surrounding conditions		
	Min. temperature range [°C]	5
	Max. temperature range [°C]	35
	Min. humidity range [% RH]	35
	Max. humidity range [% RH]	100
Electrical values		
	Mains connection	230 V/50 Hz
	Nominal current consumption [A]	3.6
	Power input [kW]	0.775
	Recommended fusing [A]	10
	Required current starting phase [A]	—
Compressor		
	Rotary piston compressor	■
	Reciprocating piston compressor	—
	Type of cooling agent	R-410A
	Amount of cooling agent [g]	290
	GWP factor	2,088
	CO_2 equivalent [t]	0.606
	Suction Side pressure [MPa]	1.5
	Discharge Side Pressure [MPa]	4.2
Water tank		
	Contents in [l]	6
Sound values		
	Distance 1 m [dB(A)]	51
Dimensions		
	Length (packaging excluded) [mm]	282
	Width (packaging excluded) [mm]	392
	Height (packaging excluded) [mm]	616
Weight		
	(packaging excluded) [kg]	19.8

NOTA: Aceasta fisa a fost realizata sub rezerva modificarilor ulterioare de ordin tehnic sau a erorilor de editare.

Fotografia are caracter informativ.

NOTE: Products and specifications are subject to change without prior notice .Pictures may differ from original.