SC METROMAT SRL

Compartimentul Comercial: 505600 - Sacele - Piata Libertatii nr.2 - tel/fax: 0268 275 212; 0268 276 807 **e-mail: sales@metromat.ro - comert@metromat.ro**

Mrcrometre digitale 0 … 25mm pana la 100mm / 0.001mm

Digital-Bügelmessschrauben Präzisionsausführung

Digital external micrometers Precision model

Hartmetall
Tungsten carbide

- DIN 863
- großes LCD Display
- Hartmetallmessflächen Ø6,5mm
- Spindenklemmung mit Hebel
- Gefühlsratsche
- Messkraft 5 – 10 N
- Handwärmeschutz
- Lieferung im Etui; ab 25 – 50mm mit Einstellmaß

Funktionen:
- Ein/Aus
- mm/inch Umschaltung
- O-Punkt an jeder Position
- Preset Funktion
- Datenausgang Variabel

- DIN 863
- Large LCD display
- Tungsten carbide-tipped measuring faces Ø6.5mm
- Spindle clamping with lever
- Ratchet stop
- Measuring force 5 – 10 N
- Insulated pads
- Delivered in a case; from 25 – 50mm with setting gauge

Functions:
- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function
- Data output Variabel



No. 2015 101

mm	inch approx.	mm	inch	kg	№
0 – 25	0 – 1	0,001	.00005	0,3	**2015 101**
25 – 50	1 – 2	0,001	.00005	0,4	**2015 102**
50 – 75	2 – 3	0,001	.00005	0,5	**2015 103**
75 – 100	3 – 4	0,001	.00005	0,55	**2015 104**
Datenkabel RS232 (2m) / Data cable RS232 (2m)					**1850 273**
Datenkabel USB (2m) / Data cable USB (2m)					**1850 274**

Digital-Bügelmessschrauben STANDARD

Digital external micrometers STANDARD

TOP
Hartmetall
Tungsten carbide

- DIN 863
- Schutzart IP54
- großes LCD Display
- Hartmetallmessflächen Ø6,5mm
- Spindelsteigung 0,5mm
- Spindelklemmung mit Hebel
- Gefühlsratsche
- Messkraft 5 – 10 N
- Handwärmeschutz
- Lieferung im Etui ab 25 – 50mm mit Einstellmaß

Funktionen:
- Ein/Aus
- mm/inch Umschaltung
- O-Punkt an jeder Position
- Preset Funktion
- ABS/INC umschaltbar

- DIN 863
- Protection class IP54
- Large LCD display
- Tungsten carbide-tipped measuring faces Ø6.5mm
- Spindle pitch 0.5mm
- Spindle clamping with lever
- Ratchet stop
- Measuring force 5 – 10 N
- Insulated pads
- Delivered in a case; from 25 – 50mm with setting gauge

Functions:
- On/Off
- mm/inch commutation
- Zero setting at any position
- Preset function
- ABS/INC reversible



No. 5000 201

mm	inch approx.	mm	inch	kg	№
0 – 25	0 – 1	0,001	.00005	0,27	**5000 201**
25 – 50	1 – 2	0,001	.00005	0,32	**5000 202**
50 – 75	2 – 3	0,001	.00005	0,47	**5000 203**
75 – 100	3 –4	0,001	.00005	0,61	**5000 204**
100 – 125	4 – 5	0,001	.00005	0,57	**5000 205**
125 – 150	5 – 6	0,001	.00005	0,72	**5000 206**

Fotografia are caracter informativ. Aceasta fisa a fost realizata sub rezerva modificarilor de ordin tehnic ulterioare sau a erorilor de editare.

Products and specifications are subject to change without prior notice.